

Colorfarm® 15

Pre-finished steel for single skin agricultural building envelopes



Designed for single skin agricultural buildings, Colorfarm® 15 provides good corrosion and high impact resistance on both the exterior and interior of the building.

Key features

- Double sided 35 µm coating for good chemical resistance inside and out.
- G275 galvanised substrate.
- Available in 6 colours, specifically developed to harmonise with the rural environment.
- 15 year functional performance guarantee.

Colorcoat® reassurance

Corus provides high quality pre-finished steel products, services and technical support under the internationally recognised Colorcoat® brand. The Colorcoat® brand provides the recognised mark of quality and metal envelope expertise from Corus. Encompassing over forty years of innovation, strict testing procedures and manufacturing excellence, Colorcoat® provides a range of pre-finished steel products which have been used on countless projects worldwide.

Colorfarm® 15

Product performance

Colorfarm® 15 is carefully manufactured in a controlled process to ensure consistent quality.

Colorfarm® 15 has been developed as an effective cladding material for agricultural buildings and is guaranteed to give 15 years functional performance, providing buildings are well designed and ventilated. Appropriate maintenance will considerably extend the overall life of Colorfarm® 15 sheeting.

Colorfarm® 15 provides good levels of resistance against many chemicals found in agricultural environments.

Corus has a range of Colorcoat® products suitable for different environments and applications. Contact Corus for more information.

Colour range

Colorfarm® 15 offers a choice of 6 colours, detailed below, which can be used for either exterior or interior surfaces.



Chalk white



Slate grey



Kiln red



Juniper green



Millstone brown



Slate blue

Product testing

To ensure the integrity of Colorcoat® products, Corus uses laboratory tests to measure their performance against corrosion, effect of sunlight, chemicals and abrasion. All testing of products is carried out in accredited laboratories to international standards.

Typical properties

Colorfarm® 15	Test standard	
Gloss (60°)	30 - 40 %	EN 13523 - 2
Resistance to rapid deformation	16 J	EN 13523 - 5
Adhesion after indentation (7.5 mm)	100 %	EN 13523 - 6
T bend (no cracking) diameter	4 T @ 16° C	EN 13523 - 7
Scratch resistance	> 3000 g	EN 13523 - 12
Abrasion resistance	< 15 mg	EN 13523 - 16
Corrosion resistance –		
Salt spray	>1000 hours	EN 13523 - 8
Humidity	>1000 hours	EN 13523 - 25
Max. continuous operating temperature	100° C	–
Min. forming temperature	16° C	–

General notes

- The figures contained in this table are typical properties and do not constitute a specification. These figures relate to the topcoat and solid colours. For details on test methods see www.colorcoat-online.com
- The printed colours shown for Colorfarm 15 are for guidance only. For true representation of colour and effect, please obtain product samples from the Colorcoat Connection helpline.
- If an exact match between components and Colorfarm 15 is essential, this is best achieved by matching to the actual cladding delivered to site.

Contact details

Corus Colors

Shotton Works
Deeside
Flintshire
CH5 2NH

Colorcoat Connection® helpline

T: +44 (0)1244 892434

F: +44 (0)1244 892321

T: EIRE +353 (0) 1297 3365

Trademarks of Corus

Colorfarm, Colorcoat, Colorcoat Connection and Juniper Green are trademarks of Corus.

Corus is part of the Tata Steel group.

Care has been taken to ensure that the contents of this publication are accurate, but Tata Steel UK Limited and its subsidiaries do not accept responsibility or liability for errors or information that is found to be misleading. Suggestions for, or descriptions of, the end use or application of products or methods of working are for information only and Tata Steel UK Limited and its subsidiaries accept no liability in respect thereof.

Before using products or services supplied or manufactured by Tata Steel UK Limited and its subsidiaries, customers should satisfy themselves as to their suitability.

Corus cares about the environment – this datasheet is printed with biodegradable vegetable inks and using material with at least 80% recycled content.

Copyright 2008 Corus
Language: English 1208